



**SAFETY DATA SHEET**  
WALKER - PENETRATING FLUID

Page: 1

Compilation date: 12/05/2015

Revision No: 1

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** WALKER - PENETRATING FLUID

**Product code:** 1470

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** PC24: Lubricants, greases, release products.

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Granville Oil & Chemicals Ltd.

Unit 29 Goldthorpe Industrial Estate

Goldthorpe

Rotherham

South Yorkshire

S63 9BL

United Kingdom

**Tel:** +44 (0)1709 890099

**Fax:** +44 (0)1709 891121

**Email:** [technical@granvilleoil.com](mailto:technical@granvilleoil.com)

**1.4. Emergency telephone number**

**Emergency tel:** +44 (0)1709 890099

(office hours only)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** Flam. Aerosol 1: H222; -: H229

**Most important adverse effects:** Extremely flammable aerosol. Pressurised container: May burst if heated.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame



**Precautionary statements:** P102: Keep out of reach of children.

[cont...]

# SAFETY DATA SHEET

## WALKER - PENETRATING FLUID

Page: 2

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### ALIPHATIC DISTILLATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-150-3	64742-48-9	-	Flam. Liq. 3: H226; Asp. Tox. 1: H304	30-50%

##### BUTANE

203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
-----------	----------	--	-------------------------------------	--------

##### SODIUM SULPHONATE - REACH registered number(s): 01-2119527859-22-0000

271-781-5	68608-26-4	-	Eye Irrit. 2: H319	1-10%
-----------	------------	---	--------------------	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. If conscious, give half a litre of water to drink immediately.  
Consult a doctor.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** No symptoms.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Nausea and stomach pain may occur. There may be vomiting. There may be loss of consciousness.

**Delayed / immediate effects:** Headaches or general malaise may result.

[cont...]

**SAFETY DATA SHEET**  
WALKER - PENETRATING FLUID

Page: 3

**4.3. Indication of any immediate medical attention and special treatment needed**

**Immediate / special treatment:** Not applicable.

**Section 5: Fire-fighting measures**

**5.1. Extinguishing media**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Dry chemical powder. Use water spray to cool containers.

**5.2. Special hazards arising from the substance or mixture**

**Exposure hazards:** Extremely flammable. In combustion emits toxic fumes. Vapour may travel considerable distance to source of ignition and flash back.

**5.3. Advice for fire-fighters**

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**Section 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Eliminate all sources of ignition.

**6.2. Environmental precautions**

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**6.4. Reference to other sections**

**Reference to other sections:** Refer to section 8 of SDS.

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Ensure there is sufficient ventilation of the area. Smoking is forbidden. Use non-sparking tools. Avoid direct contact with the substance.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight. Ensure lighting and electrical equipment are not a source of ignition.

**Suitable packaging:** Must only be kept in original packaging.

[cont...]

**SAFETY DATA SHEET**  
WALKER - PENETRATING FLUID

Page: 4

**7.3. Specific end use(s)**

Specific end use(s): No data available.

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Hazardous ingredients:**

**BUTANE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1450 mg/m3	1810 mg/m3	-	-

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Respiratory protection not required.

**Hand protection:** Protective gloves. (tested to EN374)

**Eye protection:** Safety glasses.

**Skin protection:** Protective clothing.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Aerosol

**Odour:** Characteristic odour

**Solubility in water:** Insoluble

**Flash point°C:** -74

**Relative density:** 0.664

**VOC g/l:** 943

**9.2. Other information**

**Other information:** Not applicable.

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**Reactivity:** Stable under recommended transport or storage conditions.

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

**10.3. Possibility of hazardous reactions**

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

[cont...]

**SAFETY DATA SHEET**  
WALKER - PENETRATING FLUID

Page: 5

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat. Flames. Sources of ignition.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

**Toxicity values:** No data available.

**Symptoms / routes of exposure**

**Skin contact:** No symptoms.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Nausea and stomach pain may occur. There may be vomiting. There may be loss of consciousness.

**Delayed / immediate effects:** Headaches or general malaise may result.

**Section 12: Ecological information**

**12.1. Toxicity**

**Ecotoxicity values:** No data available.

**12.2. Persistence and degradability**

**Persistence and degradability:** Biodegradable.

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** No bioaccumulation potential.

**12.4. Mobility in soil**

**Mobility:** Insoluble in water.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**12.6. Other adverse effects**

**Other adverse effects:** No data available.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

[cont...]

**SAFETY DATA SHEET**  
WALKER - PENETRATING FLUID

Page: 6

**Disposal of packaging:** Dispose of as normal industrial waste.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**14.1. UN number**

**UN number:** UN1950

**14.2. UN proper shipping name**

**Shipping name:** AEROSOLS

**14.3. Transport hazard class(es)**

**Transport class:** 2

**14.4. Packing group**

**14.5. Environmental hazards**

**Environmentally hazardous:** No

**Marine pollutant:** No

**14.6. Special precautions for user**

**Special precautions:** No special precautions.

**Tunnel code:** D

**Transport category:** 2

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Specific regulations:** Not applicable.

**15.2. Chemical Safety Assessment**

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H226: Flammable liquid and vapour.

H229: Pressurised container: May burst if heated

H304: May be fatal if swallowed and enters airways.

H319: Causes serious eye irritation.

[cont...]

**SAFETY DATA SHEET**  
WALKER - PENETRATING FLUID

**Page: 7**

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.